



US 20210094654A1

(19) **United States**

(12) **Patent Application Publication**
FUJITA

(10) **Pub. No.: US 2021/0094654 A1**

(43) **Pub. Date: Apr. 1, 2021**

(54) **BICYCLE REAR SPROCKET ASSEMBLY**

B60B 27/00 (2006.01)

B60B 27/04 (2006.01)

(71) Applicant: **SHIMANO INC.**, Sakai City (JP)

(52) **U.S. Cl.**

CPC **B62M 9/10** (2013.01); **B60B 27/023**

(2013.01); **B60B 27/04** (2013.01); **B60B**

27/0052 (2013.01); **F16H 55/30** (2013.01)

(72) Inventor: **Hiroshi FUJITA**, Sakai City (JP)

(73) Assignee: **SHIMANO INC.**, Sakai City (JP)

(21) Appl. No.: **17/118,609**

(57)

ABSTRACT

(22) Filed: **Dec. 11, 2020**

Related U.S. Application Data

(63) Continuation of application No. 15/851,781, filed on Dec. 22, 2017, which is a continuation-in-part of application No. 15/712,388, filed on Sep. 22, 2017, now abandoned.

A bicycle rear sprocket assembly comprises a plurality of bicycle sprockets comprising a first sprocket and a second sprocket. The first sprocket includes a first opening having a first minimum diameter that is smaller than a minimum outer diameter of a sprocket support body of a bicycle rear hub assembly. The second sprocket includes a second opening and at least ten internal spline teeth. The second opening has a second minimum diameter that is equal to or larger than the minimum outer diameter. The at least ten internal spline teeth are configured to engage with the sprocket support body of the bicycle rear hub assembly. The at least ten internal spline teeth include a plurality of internal-spline driving surfaces each including a radial length. A total of the radial lengths of the plurality of internal-spline driving surfaces is equal to or larger than 7 mm.

Publication Classification

(51) **Int. Cl.**

B62M 9/10 (2006.01)

B60B 27/02 (2006.01)

F16H 55/30 (2006.01)

